

## Product Introduction

This series is a stationary, automatic and silent air compressor, which has fully enclosed structure and low noise. It's applicable for use in firefighting, diving, chemical, mining, rescue, etc. This series is driven by three-phase motor.

## Features

- Air quality conforms to EN12021
- CE, CCS, ISO9001 certificates
- 4 stage compression design
- Cooling method: air cooling
- Lubrication method: oil pump
- PLC intelligent control
- Functions: emergency switch, automatic start, automatic stop, automatic condensate drain, low oil level protection, phase sequence protection, filter expiration reminder, etc




## Technical Data

Model	NRX400	NRX450
Charging rate (L/min)	400	450
Max. pressure (bar)	420	420
Number of stages	4	4
Drive	Three-phase 380V,50HZ	Three-phase 380V,50HZ
Speed (rpm)	1640	1740
Power (kw)	9	11
Horse (hp)	12	15
Weight (kg)	525	531
Dimension (mm)	910*1300*1400	910*1300*1400
Air supply interface	G5/8"	G5/8"

Note: Motors with different voltages of 50HZ or 60HZ can be customized.


## Standard Configuration




Filling hose 1.2M  
2PCS



Activated carbon  
filter cartridge




Intake filter




Oil filter



Filling valve 2PCS




2 Filling connections




Lubricating oil 3L

## Optional Configuration




DIN/INT Adaptor



4 Filling connections

## Product Details



Compressor block



PLC control panel